

HK INSTRUMENTS Ltd

Kelhästie 7
FIN-40950 MUURAME
FINLAND

www.hkinstruments.fi

Tel. +358 14 337 2000
Fax. +358 14 337 2020
Email: info@hkinstruments.fi

Bank: Leonia 800019-01847385
Vat Reg: FI 08730729
Reg no: 404.989

DIFFERENTIAL PRESSURE GAUGE



Model summary

Model	Pressure range (Pa)
DPG60	0-60 Pa
DPG100	0-100 Pa
DPG120	0-120 Pa
DPG200	0-200 Pa
DPG250	0-250 Pa
DPG300	0-300 Pa
DPG400	0-400 Pa
DPG500	0-500 Pa
DPG600	0-600 Pa
DPG800	0-800 Pa
DPG1k	0-1 kPa
DPG1,5k	0-1,5 kPa
DPG2k	0-2 kPa
DPG3k	0-3 kPa
DPG5k	0-5 kPa

Accessories

Standard accessories*:

- 2 fixing screws
- 2 plastic duct connectors
- 2 m tube \varnothing 4 / 7 mm
- surface mounting plate

Optional accessories**:

- metallic duct connectors
- flush mounting kit

*included in the sales package

** available separately

Technical data

Materials	Housing	ABS
	Cover	PC
	Membrane	silicone
	Machinery	Aluminium and steel spring
Accuracy	$\pm 2\% \text{ F.S (20}^\circ\text{C)}$, (DPG60 $\pm 4\%$; DPG100 $\pm 3\%$)	
Dial hole size	$\varnothing 110 \text{ mm}$	
Weight	234 grams	
Ambient conditions	Operation	-5... +60°C
	Storage	-40...+85°C

Mounting position Vertical

Dimensions

