



Application:	Air conditioning applications
Typ:	Bagfilter
Frame:	Plastic moulded (includes recycled materials)
Media:	Glass fiber
Max airflow:	1,25 x nominal flow
Max temp:	Max 70°C
Installation options:	Front and side access housings and frames
Relative Humidity (RH):	100%
P-marking:	* after the article number

Article number	Article namn	Article name 2	Pressure drop/Airflow (Pa/m3/h)	Filter area (m2)	Energy-class	Energy (kWh)
610162*	HI-FLO II XLT 7 / 520	HFGX-F7-592/592/520-10	75/3400	6,1	B	1031
610957*	HI-FLO II XLT 7 / 520	HFGX-F7-592/287/520-10	75/1700	3,0	B	
610163*	HI-FLO II XLT 7 / 520	HFGX-F7-287/592/520-5	75/1700	3,0	B	
612796*	HI-FLO II XLT 7 / 520	HFGX-F7-592/490/520-10	75/2700	5,4	B	
610159*	HI-FLO II XLT 7 / 520	HFGX-F7-592/592/370-10	100/3400	4,3	D	1643
610165*	HI-FLO II XLT 7 / 640	HFGX-F7-592/592/640-10	70/3400	7,5	A	918
610958*	HI-FLO II XLT 7 / 640	HFGX-F7-592/287/640-10	70/1700	3,3	A	
610166*	HI-FLO II XLT 7 / 640	HFGX-F7-287/592/640-5	70/1700	3,7	A	
616320	HI-FLO II G	HFGP-F7-320/400/520-5		2,2		
620267	HI-FLO II G	HFGP-F7-550/315/520-10		3,5		
622097	HI-FLO II G	HFGP-F7-550/470/520-9		4,6		
614008	HI-FLO II G	HFGP-F7-650/287/320-11		2,0		
602374	HI-FLO II G	HFGP-F7-736/287/370-11		2,0		
614009	HI-FLO II G	HFGP-F7-790/287/370-13		3,0		
622093	HI-FLO II G	HFGP-F7-790/375/400-13		4,2		
622095	HI-FLO II G	HFGP-F7-892/315/520-15		5,3		
614010	HI-FLO II G	HFGP-F7-892/380/520-15		4,5		
614011	HI-FLO II G	HFGP-F7-892/409/370-15		4,8		
602440	HI-FLO II	HFGS-F7-592/792/520-9		7,5		
614012	HI-FLO II G	HFGX-F7-592/400/520-10		4,4		