



Application:	Air conditioning applications
Typ:	Bagfilter
Frame:	Plastic moulded (includes recycled materials)
Media:	Glass fiber
Max airflow:	1,25 x nominal flow
Max temp:	Max 70°C
Installation options:	Front and side access housings and frames
Relative Humidity (RH):	100%
P-marking:	* after the article number

Article number	Article namn	Article name 2	Pressure drop/Airflow (Pa/m3/h)	Filter area (m2)	Energy-class	Energy (kWh)
610171*	HI-FLO II XLT 9 / 520	HFGX-F9-592/592/520-10	145/3400	6.1	D	2130
610959*	HI-FLO II XLT 9 / 520	HFGX-F9-592/287/520-10	145/1700	3,0	D	
610172*	HI-FLO II XLT 9 / 520	HFGX-F9-287/592/520-5	145/1700	3,0	D	
610174*	HI-FLO II XLT 9 / 640	HFGX-F9-592/592/640-10	135/3400	7,5	D	2016
612854*	HI-FLO II XLT 9 / 640	HFGX-F9-592/287/640-10	135/1700	3,3	D	
610175*	HI-FLO II XLT 9 / 640	HFGX-F9-287/592/640-5	135/1700	3,7	D	
614331	HI-FLO II G	HFGP-F9-736/287/370-11		3,0		
614011	HI-FLO II G	HFGP-F9-892/409/370-15		4,8		
622128	HI-FLO II	HFGS-F9-592/792/520-9		7,5		